



**LEATHER SPECIFICATIONS**

THICKNESS ASTM D1813	1.0-1.2 mm
WEIGHT ASTM D 3776	2.5 oz/sq ft
SIZE	45-48 square feet avg.
ABRASION ASTM D3884 (TABER 5130)	Weight 500 g Wheels H-18 Cycles 300
COLOR CROCK AATCC-8 (CROCKMETER CM-5) AATCC RATING	Weight 4 lbs. Wet/Dry Rub 10 Cycles 4 Minimum
FLAMMABILITY	FMVSS-302
FLEX ASTM D2097	20,000 Cycles
LIGHTFASTNESS SAE 11885 AATCC RATING	200 Hours 4 Minimum
LIGHT COMPATIBILITY (DATA COLOR)	D65 Daylight with UV CWF (cool white fluorescent) A Tungsten Light

**HOW TO ORDER LEATHER**

Leather is sold by the hide on a square foot basis. Whole hides run about 45-55 square feet. Half hides are cut from head to butt of the hide. Equivalentents of leather (square feet to fabric yardage) are shown below:

**SQUARE FEET IN LEATHER TO 54" FABRIC**

- 17 square feet = 1 yard
- 34 square feet = 2 yards
- 51 square feet = 3 yards
- 68 square feet = 4 yards
- 85 square feet = 5 yards
- 102 square feet = 6 yards
- 119 square feet = 7 yards
- 136 square feet = 8 yards
- 153 square feet = 9 yards
- 170 square feet = 10 yards

